



A VANTAGE Company

#1 Hollister-Whitney Pkwy  
Quincy, IL 62305  
Phone: 217-222-0466  
Fax: 217-222-0493

Hollister-Whitney  
ELEVATOR CO. LLC

www.hollisterwhitney.com  
sales@hollisterwhitney.com  
layouts@hollisterwhitney.com  
engineering@hollisterwhitney.com

## HOLLISTER-WHITNEY VVVF LOW-SLIP HOIST MOTOR DATA OPEN DRIP PROOF - 208/230/460 VAC

	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	1200 SRPM VERSION	5	208 / 230 / 460	566	256T	1165	15.9 - 15.2 / 7.6
7-1/2		208 / 230 / 460	864	256T	1165	24.2 - 23.8 / 11.9	225
10		208 / 230 / 460	1042	256T	1165	30.6 - 31.0 / 15.5	225
12-1/2		208 / 230 / 460	1192	284T	1165	34.3 - 33.2 / 16.6	300
15		208 / 230 / 460	1416	284T	1165	43.3 - 43.0 / 21.5	300
20		208 / 230 / 460	1754	286T	1165	52.0 - 54.6 / 27.3	325
25		208 / 230 / 460	2240	324T	1170	71.6 - 66.2 / 33.1	400
30		208 / 230 / 460	2322	326T	1175	83.4 / 81.0 / 40.9	450
40		208 / 230 / 460	3395	365T	1165	103.0 / 98.2 / 49.1	610
50		208 / 230 / 460	4056	365T	1165	130.0 - 126.0 / 63.0	610
60		208 / 230 / 460	4312	365T	1170	152.0 / 144.6 / 72.3	610
75		208 / 230 / 460	5596	405T	1170	184.0 - 172.0 / 86.0	865
900 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	5	208 / 230 / 460	679	256T	870	21.0 - 20.0 / 10.0	225
	7-1/2	208 / 230 / 460	1011	256T	870	30.0 - 30.0 / 15.0	225
	10	208 / 230 / 460	1091	284T	870	33.4 - 30.8 / 15.4	300
	12-1/2	208 / 230 / 460	1401	286T	870	40.0 - 40.0 / 20.0	325
	15	208 / 230 / 460	1548	286T	870	49.0 - 49.0 / 24.5	325
	20	208 / 230 / 460	1888	324T	870	65.0 - 64.0 / 32.0	400
	25	208 / 230 / 460	2240	326T	875	79.5 - 76.6 / 38.3	450
	30	208 / 230 / 460	2803	364T	870	88.0 - 84.0 / 42.0	550
	40	208 / 230 / 460	3549	365T	870	124.0 - 112.0 / 56.0	610
50	208 / 230 / 460	4009	405T	870	148.0 - 134.0 / 67.0	865	
1800 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	5	208 / 230 / 460	727	256T	1760	15.5 - 15.0 / 7.5	225
	7-1/2	208 / 230 / 460	1003	256T	1760	24.3 - 22.8 / 11.4	225
	10	208 / 230 / 460	1051	256T	1760	28.0 - 25.4 / 12.7	225
	12-1/2	208 / 230 / 460	1192	284T	1760	33.4 - 30.0 / 15.0	300
	15	208 / 230 / 460	1387	284T	1760	40.0 - 39.6 / 19.8	300
	20	208 / 230 / 460	1773	284T	1760	54.2 - 48.8 / 24.4	300
	25	208 / 230 / 460	2028	286T	1760	68.6 - 62.6 / 31.3	325
	30	208 / 230 / 460	2377	324T	1760	75.0 - 70.0 / 35.0	400
	40	208 / 230 / 460	3096	326T	1760	102.0 - 91.0 / 45.5	450
	50	208 / 230 / 460	3685	364T	1760	128.5 - 116.0 / 58.0	550
	60	208 / 230 / 460	4312	365T	1760	152.0 - 138.0 / 69.0	610
75	208 / 230 / 460	5117	365T	1760	188.0 - 170.0 / 85.0	610	

All Models have 35 foot Encoder Cables  
Standard Encoder is 2048 PPR; also available in 1024 PPR  
Constant Torque 0-60 Hz  
Variable Torque 60-90 Hz  
60 Minute Duty - Inverter Duty  
Extended End Play  
Foot Mount Motors

BULLETIN 1145  
05-19-2010 MJC  
04-16-2011 MJC  
PUR 793 08-09-2016 KLG  
05-28-2019 TJP  
05-10-2020 TJP



A VANTAGE Company

#1 Hollister-Whitney Pkwy  
Quincy, IL 62305  
Phone: 217-222-0466  
Fax: 217-222-0493

Hollister-Whitney  
ELEVATOR CO. LLC

www.hollisterwhitney.com  
sales@hollisterwhitney.com  
layouts@hollisterwhitney.com  
engineering@hollisterwhitney.com

## HOLLISTER-WHITNEY VVVF LOW-SLIP HOIST MOTOR DATA OPEN DRIP PROOF - 575 VAC

	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 575V	WEIGHT (LBS.)
1200 SRPM VERSION	5	575	566	256T	1165	5.6	225
	7-1/2	575	864	256T	1165	8.4	225
	10	575	1042	256T	1165	10.5	225
	12-1/2	575	1192	284T	1165	11.9	300
	15	575	1416	284T	1165	15.2	300
	20	575	1754	286T	1165	20.1	325
	25	575	2240	324T	1170	24.8	400
	30	575	2322	326T	1175	28.1	450
	40	575	3395	365T	1165	38.6	610
	50	575	4056	365T	1165	46.5	610
	60	575	4312	365T	1170	53.0	610
	75	575	5596	405T	1170	66.7	865
900 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 575V	WEIGHT (LBS.)
	5	575	679	256T	870	6.4	225
	7-1/2	575	1011	256T	870	11.4	225
	10	575	1091	284T	870	11.8	300
	12-1/2	575	1401	286T	870	15.6	325
	15	575	1548	286T	870	17.7	325
	20	575	1888	324T	870	23.0	400
	25	575	2240	326T	875	28.4	450
	30	575	2803	364T	870	32.5	550
	40	575	3549	365T	870	43.0	610
50	575	4009	405T	870	50.0	865	
1800 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 575V	WEIGHT (LBS.)
	5	575	727	256T	1760	5.2	225
	7-1/2	575	1003	256T	1760	8.4	225
	10	575	1051	256T	1760	9.8	225
	12-1/2	575	1192	284T	1760	11.4	300
	15	575	1387	284T	1760	13.8	300
	20	575	1773	284T	1760	18.5	300
	25	575	2028	286T	1760	22.3	325
	30	575	2377	324T	1760	26.4	400
	40	575	3096	326T	1760	35.2	450
	50	575	3685	364T	1760	44.2	550
	60	575	4312	365T	1760	52.3	610
75	575	5117	365T	1760	67.9	610	

All Models have 35 foot Encoder Cables  
Standard Encoder is 2048 PPR; also available in 1024 PPR  
Constant Torque 0-60 Hz  
Variable Torque 60-90 Hz  
60 Minute Duty - Inverter Duty  
Extended End Play  
Foot Mount Motors

BULLETIN 1145  
05-19-2010 MJC  
04-16-2011 MJC  
PUR 793 08-09-2016 KLG  
05-28-2019 TJP  
05-10-2020 TJP